



# ARKFEO

**A sanding tool specially  
for soft or resinous woods.**

*Woods such as pine or spruce have a high resin content, which often leads to clogging of the abrasive material, and makes sanding as well as the subsequent surface treatment more difficult. For these woods, Ekamant has now developed ARKFEO, with an extra open coat distribution of sharp aluminium oxide grain.*

- To get the best result from ARKFEO, comparatively low sanding pressure should be used. This will result in a smoother surface finish, and easier intermediate lacquer sanding, and with reduced stress on the abrasive material, a substantially improved service life.
- The bond system is designed with a high gloss surface, which together with an extra open coat grit distribution reduces clogging with resin and fibre residue to a minimum.
- Ekamant - the inventor of antistatic abrasive materials, continues to develop this technology giving improved antistatic qualities for ARKFEO. Our clear leadership in this field results in even better sanding economy and working environment.



Backing material	F-paper
Type of grains	Aluminium Oxide
Coating	Extra open
Binder	Resin over resin
Antistatic treatment	Yes
Stearated	No

Item	standard
Narrow belts	Yes
Wide belts	Yes max 1400 mm
Rolls	Yes
Discs	No
Sheets	No

12  
16  
20  
24  
30  
36  
40  
50  
60  
80  
100  
120  
150  
180  
220  
240  
280  
320  
360  
400  
500  
600  
800  
1000  
1200

**grit sizes**



Ekamant AB · Box 114 · SE-285 23 Markaryd, Sweden  
Tel. +46-433-79700 · Fax +46-433-79797  
E-mail: sales@ekamant.se