



# ARKFO

## A versatile sanding tool for most types of wood.

*It has been difficult to find an effective sanding tool for furniture and joinery manufacturers, which will excel on both solid wood as well as veneer applications. For these sanding applications, Ekamant has now developed ARKFO, which combines the capacity for high rates of stock removal with the ability to produce excellent surface finishes.*

- To get the best result from the unique sharpness of ARKFO, comparatively low sanding pressure should be used. This will give minimal fibre rise, a more even stain, with potentially less lacquer consumption, and easier intermediate lacquer sanding.
- The bond system is designed with a high gloss surface, which together with open coat grit distribution reduces clogging to a minimum, and contributes to the best possible sanded finish. However, if greater clogging problems exist, then we recommend the use of the product ARKFEO for coarse and intermediate sanding, and ARKFO for the finish sanding.
- Ekamant - the inventor of antistatic abrasive materials, continues to develop this technology, giving improved antistatic qualities for ARKFO. Our clear leadership in this field results in even better sanding economy and working environment.



Backing material	F-paper
Type of grains	Aluminium Oxide
Coating	Open
Binder	Resin over resin
Antistatic treatment	Yes
Stearated	No

Item	standard
Narrow belts	Yes
Wide belts	Yes max 1400 mm
Rolls	Yes
Discs	No
Sheets	No

12  
16  
20  
24  
30  
36  
40  
50  
60  
80  
100  
120  
150  
180  
220  
240  
280  
320  
360  
400  
500  
600  
800  
1000  
1200

grit sizes



Ekamant AB · Box 114 · SE-285 23 Markaryd, Sweden  
Tel. +46-433-79700 · Fax +46-433-79797  
E-mail sales@ekamant.se